



 OS-203DT

OS-203DT

OS-203DT comes complete with ArgoBar, the powerful label design software that allows you to design barcode labels within minutes. In addition, it supports both PPLA and PPLB programming languages for compatibility with other printers.

Designed with the most recent advanced technology, this printer features a built-in tear bar and it can also be easily reconfigured. You buy only the features your current application requires, with the assurance that the printer can also accommodate your future business needs.

Argox can.

ARGOX
Empower the Barcode



Offer superior quality at
the lowest possible cost?

Specifications	OS-203DT
Printing Method	Direct Thermal
Printing Resolution	203 dpi (8 dots/mm)
Printing Speed	2 ~ 3.5 ips (51 ~ 88.9 mm/s)
Printing Length	1" ~ 10" (25 ~ 254 mm)
Printing Width	Max 2.83" (72mm)
Memory	512KB DRAM, 512KB Flash ROM
CPU Type	16 bit RISC, microprocessor
Media Sensor	Reflective
Display	LED indicators x 2
Operation Interface	Button x 1
Communication Interface	Centronics parallel RS-232 Min Din 6P
Fonts	Int'l character sets standard 5 alpha-numeric fonts from 0.049"H ~ 0.23"H (1.25mm ~ 6.0mm) All fonts are expandable up to 24 x 24 4 direction 0° ~ 270° rotation Soft fonts are downloadable
Barcodes	Code 39, Extended Code 39, Code 93, Code 128 UCC Code 128 (Subset A, B, C) Codabar, Interleave 2 of 5, EAN-8 2&5 add on, EAN-13, EAN-128, UPC, UPC-A, E 2&5 add on, POSTNET, German POST, Matrix 25, Maxicode, PDF-417
Graphics	PCX, bit map, IMG, HEX, GDI graphics
Software	Argox PPLA/PPLB Language Windows Driver (Win 98/2000/NT/XP) Label editing software - ArgoBar Print Utility
Media	Roll-feed, die-cut, continuous, fan-fold, tags, ticket in thermal paper or plain paper Max width 2.83" (71.88mm) Min width 1.0" (25.4mm) Thickness 0.0025" ~ 0.01" (0.0635mm ~ 0.254mm) Max roll capacity 4.3" (109mm) OD Core size 1" (25mm) ID
Ribbon	Nil
Mechanism Request	Fan fold paper back cover, face-out ribbon run way, face-out media run way, un-adjustable TPH carrier
Dimensions	W134 x H163 x L228 mm, 2.6lbs (1.2kgs)
Power Source	21VAC or DC24V (min 2.5A) 50/60 Hz, external power adapter
Agency Listing	CE, UL, CUL, FCC, CCC
Operation Environment	40° F ~ 100° F (4° C ~ 38° C) ; 10 ~ 90% non condensing
Optional Items	Cutter, Dispenser kit, Real time clock card, ArgoNet print server, External USB connector, ArgoKee, 2MB Asian Font card (Traditional Chinese, Simplified Chinese, Korean and Japanese)

Specifications subject to change without notice